

CP55 series

Industrial Mobile Computer



| | | |
|--------------------------|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Performance | Operating System | Windows® Embedded Compact 7, Windows® Embedded Handheld 6.5.3 |
| | CPU | TI OMAP™ 4 Processors 4430 1GHz Dual Core |
| | Memory | 4GB Flash / 512MB LPDDR2 SDRAM |
| | Expansion | Micro SD card slot (up to 32GB) |
| | Operating power | Rechargeable 3.7V 3300 mAh Li-ion battery |
| | Working hours ¹ | 10 hours |
| | Alert | Tri-color LEDs, vibrator, speaker |
| | Interface supported | USB OTG, RS232, and battery Charging |
| Wireless communication | WWAN | GSM / GPRS / EDGE / WCDMA / HSDPA / HSUPA GSM/GPRS/EDGE: 850/900/1800/1900 : UMTS/HSDPA/HSUPA: 850/1900/2100 |
| | WLAN | IEEE 802.11 a/b/g/n |
| | WLAN security | WPA (PSK), WPA2 (PSK), WEP, TKIP, AES, EAP (EAP-MD5 CHAP), EAP-TLS, PEAP |
| | WPAN | Bluetooth® Class II, V2.1 with Enhanced Data Rate (EDR) |
| | Bluetooth® profile | GAP, SDP, GOEP, SPP, OPP, PAN, HID , HSP , HFP, FTP |
| | GPS | Integrated with A-GPS ready and external antenna connector |
| Data capture | Barcode scanning | Linear imager / Laser / Long range laser / 2D imager (support low contrast barcode) |
| | RFID read / write | HF RFID 13.56 MHz frequency, support ISO14443A, ISO14443B, and ISO15693 and with SAM slots |
| | Camera | 5 megapixels CMOS with LED flash and autofocus |
| Physical characteristics | Display | 3.5" 480 (W) x 640 (H) VGA / 240 (W) x 320 (H) QVGA transfective TFT color LCD with LED backlight |
| | Keypad | Numeric or QWERTY keypad with LED backlight |
| | Size (LxWxH) | 182 x 77.5 x 37 mm / 7.17 x 3.05 x 1.46 in. |
| | Weight (laser including battery) | 400g / 14.1 oz. configuration dependent |
| User environment | Operating temperature | -20°C to 50°C / -4°F to 122°F |
| | Storage temperature | -30°C to 70°C / -22°F to 158°F (w/o battery) |
| | Humidity (non-condensed) | Operating 5% to 95% / Storage 5% to 95% |
| | Impact resistance | SGS certified 1.5 m (5 ft.) multiple drops onto concrete, 5 drops on each side / IP65 / 1000 tumbles at 0.5 m |
| | Electrostatic discharge | ± 15 kV air discharge, ± 8 kV contact discharge |
| | Regulatory compliance | CE, RoHS, REACH, WEEE, ErP, BSMI, NCC, SRMC, MII, CCC, RCM (only for the configuration without 3G) |
| Development support | | Cipherlab C++ / .NET, SDK to support Microsoft® Visual Studio 2008 |
| Application software | | App-Lock, Button Assignment, GPS Viewer, Push-to-talk, Reader Configuration, Signature Capture, Terminal Emulation, CipherLab MIRROR Browser, Kalipso Mobile Application Generator, Naurtech CETerm, SOTI MobiControl, CipherLab MIRROR Browser |
| Accessories | | Charging and communication cradle, snap-on cable (USB/RS232), snap-on vehicle charger, 4 slot battery charger, pistol grip, protective cover, belt holster, belt holster for device with pistol grip |
| Warranty | | 1 year |

1. Minimum 10 hours under WLAN and laser scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a/b/g/n on. The test is based on one broadcasting packet per second.

2. The mobile computer has received general telecommunication certification for data communication. Please check with your local carrier for the optimum operating efficiency.



HEADQUARTERS

CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec.2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab Electronics Trading (Shanghai) Co., Ltd.
J Room, 4F, No.728 West Yan'an Rd.
Changning District, Shanghai
China 200050
Tel +86 21 3368 0288
Toll Free 400 920 0285
Fax +86 21 3368 0286

CipherLab USA Inc.
2552 Summit Ave. STE 400
Plano, Texas, USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

